



CreativeWEAVE

form function solution

Hydra



WORLD WIDE WEAVE



Technische Daten Technical Data Sheet / Fiche Technique / Información Técnica

Werkstoff Material / Matériau / Material	Edelstahl 1.4404 (AISI 316L) Stainless Steel / Acier inoxydable / Acero inoxidable	
Freie Fläche Open area / Surface ouverte / Superficie abierta	ca. 75 %	
Drahtstärke Wire diameter / Diamètre des fils / Diametro de hilos	Kettendraht : 2 mm Precrimped wire / fil ondulé / hilo ondulado	Schussdraht : 2 mm Precrimped wire / fil ondulé / hilo ondulado
Teilung Kettendraht Pitch precrimped wire / Entraxe fil ondulé / Paso hilo ondulado	12 mm	
Teilung Schussdraht Pitch precrimped wire / Entraxe fil ondulé / Paso hilo ondulado	20 mm	
Dicke Thickness / Epaisseur / Espesor	ca. 4,0 mm	
Gewicht Weight / Poids / Peso	ca. 3,6 kg/m ²	
Maximale Gewebebreite Maximum mesh width / Largeur maximale / Ancho máximo	4 m	
Maximale Gewebelänge Maximum mesh length / Longueur de tissu maximale/ Longitud maxima de la tela	24 m	
Standardbefestigung Standard fixing detail Fixation standard Sujeción standard	Klemmprofil Clamping profiles Profils de serrage Perfiles de aprieto	



KO & CO BENELUX nv.
Showroom
Boomssteenweg 41/10
B-2630 Aartselaar
Tel. (...32) (0)3 458 40 40
Fax (...32) (0)3 458 40 00
www.ko-co.com

