



**CreativeWEAVE**

form function solution

*Lyra 120/20*



WORLD WIDE WEAVE



## Technische Daten    Technical Data Sheet / Fiche Technique / Información Técnica

<b>Werkstoff</b> Material / Matériau / Material	<b>Edelstahl 1.4404 ( AISI 316L )</b> Stainless Steel / Acier inoxydable / Acero inoxidable	
<b>Freie Fläche</b> Open area / Surface ouverte / Superficie abierta	ca. 73 %	
<b>Drahtstärke</b> Wire diameter / Diamètre des fils / Diametro de hilos	<b>Kettendraht gerade :</b> 9 x 1,5 mm Straight wire / fil droit / hilo liso	<b>Schussdraht gekröpft:</b> 5 x 1 mm Flachband Crimped flat wire / fil plat ondulé / fleje ondulado
<b>Teilung gerader Draht</b> Pitch straight wire / Entraxe fil droit / Paso hilo liso	120 mm	
<b>Teilung gekröpfter Draht</b> Pitch precrimped wire / Entraxe fil ondulé / Paso fleje ondulado	20 mm	
<b>Dicke</b> Thickness / Epaisseur / Espesor	ca. 3,2 mm	
<b>Gewicht</b> Weight / Poids / Peso	ca. 3,9 kg/m <sup>2</sup>	
<b>Maximale Gewebebreite</b> Maximum mesh width / Largeur maximale / Ancho máximo	4 m	
<b>Maximale Gewebelänge</b> Maximum mesh length / Longueur de tissu maximale/ Longitud maxima de la tela	24 m	
<b>Standardbefestigung</b> Standard fixing detail Fixation standard Sujeción standard	<b>Klemmprofil</b> Clamping profiles Profils de serrage Perfiles de aprieto	



**KO & CO BENELUX nv.**  
Showroom  
Boomssesteenweg 41/10  
B-2630 Aartselaar  
Tel. (...32) (0)3 458 40 40  
Fax (...32) (0)3 458 40 00  
www.ko-co.com

