



CreativeWEAVE
form function solution

Vela



WORLD WIDE WEAVE



Technische Daten Technical Data Sheet / Fiche Technique / Información Técnica

Werkstoff Material / Matériau / Material	Edelstahl 1.4404 (AISI 316L) Stainless Steel / Acier inoxydable / Acero inoxidable
Freie Fläche Open area / Surface ouverte / Superficie abierta	ca. 50 %
Drahtstärke Wire diameter / Diamètre des fils / Diametro de hilos	Kettdraht gekröpft: 2 mm Schussdraht gekröpft: 2 mm Crimped wire / fil Crimped wire / fil ondulé / ondulé / hilo ondulado hilo ondulado
Teilung Kettdraht Pitch crimped wire / Entraxe fil ondulé / Paso hilo ondulado	35 mm
Teilung Schussdraht Pitch precrimped wire / Entraxe fil ondulé / Paso hilo ondulado	4,2 mm
Dicke Thickness / Epaisseur / Espesor	ca. 4,5 mm
Gewicht Weight / Poids / Peso	ca. 6,7 kg/m ²
Maximale Gewebebreite Maximum mesh width / Largeur maximale / Ancho máximo	4 m
Maximale Gewebelänge Maximum mesh length / Longueur de tissu maximale/ Longitud maxima de la tela	24 m
Standardbefestigung Standard fixing detail Fixation standard Sujeción standard	Klemmprofil Clamping profiles Profils de serrage Perfiles de aprieto

